

M A S K I N G T A P E

Venture Tape 100 is a natural colored crepe paper masking tape coated with a high grade synthetic rubber pressure sensitive adhesive (PSA). Specifically designed for corrugated and packaging applications, Venture Tape 100 is also an excellent general purpose tape.

Product Construction



← Crepe Paper

← Rubber Pressure Sensitive Adhesive

Features & Benefits

- Versatile packaging tape product meets a wide variety of application requirements
- Humidity and environmental condition resistance
- Excellent performance at high and low temperatures
- Durability under stress
- In-stock product available for immediate shipment

Test	Typical Value		Test Method
	Typical Value	(Metric)	
Product Thickness (Total)	5.8 mils	147.3 microns	PSTC-133
Peel Adhesion	32 oz/in	8.9 N/25mm	PSTC-101
Shear Strength	>24 hours	>168 hours	PSTC-107
Tensile Strength	18 lb/in	80.1 N/25mm	PSTC-131
Elongation	7 %	7 %	
Minimum Application Temperature	30 °F	0 °C	
Maximum Continuous Temperature	140 °F	60 °C	

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

- ¾" (19mm), 1" (25mm), and 2" (50mm) standard roll sizes
- Custom rolls available on request; minimum slit width 0.25" (6mm)

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076

From United Kingdom 0-800-962-957

From Australia 1-800-122-797

www.venturetape.com



USA

Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065

Europe – Venture Tape

Venture Tape Europe Corp.
Units 5 – 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia

Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield 3061 Victoria
Australia
(03) 9357 6025
FAX (03) 9357 6045