



Venture Tape

30 Commerce Road
Rockland, MA 02370-0384

10/1/2008
781-871-1400
Fax: 781-871-0065

470

4 MIL SANDBLAST VINYL TAPE

DESCRIPTION: A thin strong, conformable premium quality vinyl tape with an aggressive, removable, acrylic adhesive system. This system is designed to hold during sandblast operations and remove with no transfer to surface materials.

APPLICATIONS: Primarily used as a sandblast stencil for light blasting of glass and wood. Die cuts clean with no residue transfer upon removal.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness: (exclusive of liner)	5 mils (0.005")	0.127 mm
Adhesion:		
Peel (PSTC 1) modified		
15 min. residence		
off Stainless Steel	26 oz/inch width	7.12 N/2.5 cm
off Plexiglas	30 oz/inch width	8.21 N/2.5 cm
off Glass	26 oz/inch width	7.12 N/2.5 cm
Shear (PSTC 7) 4+ hrs @	2 psi	13.8 kPa
Color:	White, Clear	
*Standard Widths:	6", 12", 18", 24", 36", 48", 54" & 60"	152.4, 304.8, 457.2, 914.4, 1219.2, 1371.6, 1524mm
*Standard Length:	20 yards	18.24 m
* Other widths and lengths are available upon request.		

IMPORTANT INFORMATION:

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.
9/11/97