

473

4 MIL PAINT MASK

DESCRIPTION: A thin, strong, conformable premium quality vinyl film coated with an aggressive, removable, stabilized acrylic adhesive system. This system is U.V. resistant, plasticizer resistant, and heat resistant (325°F).

APPLICATIONS: Used as a paint mask for both interior and exterior applications. Die cuts cleanly with no adhesive transfer upon removal. Primarily used for automotive and aviation masking along with vinyl banner masking.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness: (exclusive of liner)	5 mils (.005")	0.127 mm
Adhesion:		
Peel (PSTC 1) modified (15 min. residence)		
off Stainless Steel	8 oz/inch width	2.26 N/2.5 cm
off Plexiglass	9 oz/inch width	2.54 N/2.5 cm
off Glass	8 oz/inch width	2.26 N/2.5 cm
Shear (PSTC #7) 4+ hr. @	2 psi	13.80 kPa
COLOR:	White	

IMPORTANT INFORMATION:

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her use; and

user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

3/19/98