



30 Commerce Road
Rockland, MA 02370

Phone: 1-800-343-1076
Fax: 781-871-0065

Technical Data Sheet

479

MOSAIC MOUNT

DESCRIPTION: A thin strong, conformable premium quality vinyl tape with an aggressive, cleanly removable, acrylic adhesive system. This system is designed to resist the mechanical and thermal forces of pouring and curing calcinate cement.

APPLICATIONS: For holding glass elements in position in the bottom of a mold used in casting mosaic garden stones, table tops, and etc. Die cuts clean with no residue transfer upon removal.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness: (exclusive of liner)	5 mils (0.005")	0.127 mm
Adhesion:		
Peel (PSTC 1) modified		
15 min. residence		
off Stainless Steel	26 oz/inch width	7.12 N/2.5 cm
off Plexiglas	30 oz/inch width	8.21 N/2.5 cm
off Glass	26 oz/inch width	7.12 N/2.5 cm
Shear (PSTC 7) 4+ hrs @	2 psi	13.8 kPa
Color:	White, Clear	
Standard Size:	20"x 10 ft. roll	508 mm x 3.05 m roll

IMPORTANT INFORMATION:

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.
10/31/03