



30 Commerce Road
Rockland, MA 02370

Phone: 1-800-343-1076
Fax: 781-871-0065

Technical Data Sheet

Product No.:

529

Description:

A self wound white paper coated with a specialty water dissolvable acrylic pressure sensitive adhesive system. The adhesive is tinted blue.

Applications:

Repluable splicing applications. A high performance splicing tape used in the manufacture of paper, plastics, and other continuous web processes. Especially suitable in the manufacture of news print. Thickness conformability is excellent for most irregular and mismatched surfaces.

TECHNICAL DATA

	<u>Imperial</u>	<u>Metric</u>
Adhesive thickness:	1.5 mils (0.0015")	0.0381 mm
Substrate Thickness:	3.1 mils (0.0031")	0.0787 mm
Peel Adhesion (PSTC-1):	35 oz/inch	10.0 N/2.5 cm
Shear Adhesion (PSTC-7):	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
Tensile (PSTC-31):	35 lbs/inch width	159 N/ 2.5 cm
Elongation:	1%	1%
Minimum Application Temperature:	-10°F	-23°C
Maximum Continuous Use Temperature:	300°F	149°C
Maximum Intermittent Temperature:	392°F	200°C

The information listed is in good faith and has been established from sources believed to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities.