

# 542

## 2 MIL UNSUPPORTED TRANSFER FILM

---

**DESCRIPTION:** A 2 mil (50 micron) unsupported acrylic transfer film.

**APPLICATIONS:** A high performance acrylic transfer tape designed for metal to metal and plastic to metal applications. Good temperature and UV resistance for interior and exterior applications. Superior heat and plasticizer resistance.

### TECHNICAL DATA

	<u>Imperial</u>	<u>Metric</u>
<b>Thickness (exclusive of liner):</b>	2.0 mil (0.002 in)	0.0506 mm
<b>Adhesion:</b>		
<b>Peel(PSTC-1):</b>	70.0 oz/inch width	20.0 N/2.5 cm
<b>Shear (PSTC-7A)48 hrs @</b>	2.2 psi	15.2 kPa
<b>Temperature Resistance:</b>	300°F	152°C
<b>Minimum Application</b>		
<b>Temperature:</b>	32°F	0°C
<b>Release Liner:</b>	55 lb bleached kraft	90 GSM

### **IMPORTANT INFORMATION:**

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her intended use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

4/2/98