



Venture Tape

30 Commerce Road
Rockland, MA 02370-0384

9/26/2008
781-871-1400
Fax: 781-871-0065

546

1.5 MIL UNSUPPORTED TRANSFER FILM

DESCRIPTION: A 1.5 mil (37.5 micron) unsupported acrylic transfer film.

APPLICATIONS: A high performance acrylic transfer tape designed for metal to metal and plastic to metal applications. Good temperature and UV resistance for interior and exterior applications. Superior heat and plasticizer resistance.

TECHNICAL DATA

| | <u>Imperial</u> | <u>Metric</u> |
|--|--------------------|---------------|
| Thickness (exclusive of liner): | 1.5 mil (0.0015") | 0.0381 mm |
| Adhesion: | | |
| Immediate Peel (PSTC-1): | 60.0 oz/inch width | 17.1 N/2.5 cm |
| Shear (PSTC-7A) 48 hrs @ | 2.2 psi | 15.2 kPa |
| Temperature Resistance: | 300°F | 152°C |
| Minimum Application | | |
| Temperature: | 32°F | 0°C |
| Release Liner: | 49 lb | 80 GSM |
| | Bleached glassine | |

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 5/5/04