



Venture Tape

30 Commerce Road
Rockland, MA 02370-0384

9/24/2008

781-871-1400
Fax: 781-871-0065

561

1/2 MIL DIFFERENTIAL DOUBLE COATED POLYESTER TAPE

DESCRIPTION: A differentially coated 1/2 mil (12 micron) polyester film coated on the exposed side with an aggressive acrylic adhesive system which has excellent adhesion to most surfaces and performs well at low temperatures as well as high. The liner side is coated with an aggressive rubber-based adhesive system which has excellent quick stick and good surface wet out to high and low energy surfaces.

APPLICATIONS: Foam and gasket material laminating tape designed for use in laminating dissimilar substrates and mounting applications of all materials.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness: <i>(exclusive of liner)</i>	3.3 mils (0.0033")	0.084 mm
Adhesion:		
Peel(PSTC-1):		
Exposed side:	64 oz/inch width	18.1 N/2.5 cm
Liner side:	96 oz/inch width	27.1 N/2.5 cm
Shear (PSTC-7):		
Exposed side: 100+ @	2 psi	13.8 kPa
Liner side: 15+ hrs @	2 psi	13.8 kPa
Tensile:	7.5 lbs/inch width	33.9 N/2.5 cm
Elongation:	100%	100%
Minimum Application		
Temperature:	35°F	2°C
Maximum Continuous Use		
Temperature: Acrylic:	220°F	105°C
Rubber:	175°F	80°C
Release Liner:	55 lb	90 GSM
	Bleached Densified Kraft	

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 7/9/96