



Venture Tape

30 Commerce Road
Rockland, MA 02370-0384

9/25/2008

781-871-1400
Fax: 781-871-0065

567

PREMIUM HIGH TACK DOUBLE COATED POLYESTER TAPE

DESCRIPTION: A 1/4 mil (.00025") polyester film coated on both sides with an extremely aggressive modified acrylic adhesive. Venture #567 exhibits very good chemical and solvent resistance. Adhesion is excellent to low energy surfaces, metals, glass, foils, paper and most engineering plastics. The thin, 1/4 mil carrier tears easily; allows for easy, clean diecutting and conformability.

APPLICATIONS: Designed for splicing paper and plastics which normally present adhesion problems. Also used in laminating of dissimilar substrates, nameplate mounting, etc.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness: (<i>exclusive of liner</i>)	3.5 mil (.0035")	0.0889 mm
Adhesion:		
Peel - Stainless Steel		
20 min. dwell:	76 oz/inch width	21.5 N/2.5 cm
2 hr. dwell:	92 oz/inch width	26.0 N/2.5 cm
Peel - Untreated Polypropylene		
20 min. dwell:	32 oz/inch width	9.1 N/2.5 cm
2 hr. dwell:	40 oz/inch width	11.3 N/2.5 cm
Shear - 15+ hr. @	2 psi	13.8 kPa
Tensile:	3 lbs/inch width	13.4 N/2.5 cm
Elongation:	100%	100%
Minimum Application		
Temperature:	20°F	-7°C
Maximum Continuous Use		
Temperature:	200°F	93°C

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 4/23/01