



Venture Tape Corp.
 30 Commerce Road
 P.O.Box 384
 Rockland, MA
 02370-0384 U.S.A.

781-331-5900
 781-871-1400
 800-343-1076 (U.S.A.)
 800-544-1024 (Canada)
 Fax: 781-871-0065
<http://www.venturetape.com>

581

DOUBLE COATED CLOTH TAPE

DESCRIPTION: A tightly woven cotton/polyester blend fabric coated on both sides with a premium grade, aggressive rubber based pressure sensitive adhesive. This high performance adhesive system exhibits very good adhesion to a wide variety of surfaces. Flexibility and thickness enhance sealing ability to rough and textured surfaces.

APPLICATIONS: Used in securing polyethylene film to brick and cinder block walls. Also used for splicing polysheeting during fabrication of pressurized environments. Can also be used to install and hold down carpeting.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness:	11 mils (.0011")	0.275 mm
Adhesion:		
Peel:	160 oz/inch width	45.2 N/2.5 cm
Shear: 96 hours @	2.2 psi	15.2 kPa
Tensile:	12 lb/inch width	54.3 N/2.5 cm
Elongation:	29%	29%
Minimum Application Temperature:	35°F	2°C
Maximum Continuous Use Temperature:	165°F	74°C
Release Liner:	55 lb.	90 GSM
	moisture stable glassine	

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 12/21/00