



Venture Tape

30 Commerce Road
Rockland, MA 02370-0384

9/25/2008

781-871-1400
Fax: 781-871-0065

585

DOUBLE COATED TISSUE TAPE

DESCRIPTION: A thin, strong, conformable tissue coated on both sides with 2 mils of a high temperature resistant acrylic adhesive. The acrylic adhesive has excellent quick stick and very high shear properties. This product performs well in a broad range of temperatures and bonds well to a variety of surfaces.

APPLICATIONS: High performance flying splice on corrugated paper, plastics and other web process materials where prolonged exposure to elevated temperatures is required. May also be used for laminating dissimilar surfaces. Good adhesion to fabrics.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness (<i>exclusive of liner</i>):	5.0 mils (.005")	0.127 mm
Adhesion:		
Peel (PSTC #3):	20 oz/inch width	5.7 N/2.5 cm
Ultimate Peel (PSTC #3):	39 oz/inch width	11.1 N/2.5 cm
Shear (PSTC #7): Indefinite @	2.2 psi	15.2 kPa
Tensile:	6 lbs/inch width	27.1 N/2.5 cm
Elongation:	5%	5%
Temperature Resistance:	-10 to 400°F	-23 to 205°C
Minimum Application		
Temperature:	40°F	4°C
Release Liner:	55 lb. super calendered kraft	90 GSM super calendered kraft

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 5/14/99