

# 794

## HIGH TACK 4 MIL (100 micron) ACRYLIC TRANSFER ADHESIVE

---

**DESCRIPTION:** An extremely aggressive, 4 mil (100 micron) clear acrylic, unsupported adhesive formulation. Excellent resistance to oxidation, UV and heat. High tack and shear. Good adhesion to metals. low surface energy plastics, most elastomers and untreated olefins.

**APPLICATIONS:** For high speed splicing, nameplates, and mounting of various material. High tack allows easy liner removal in paper splicing. For use where good balance of peel shear and heat resistance are desirable.

### TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
<b>Total Thickness:</b>	4.0 mils (.004")	0.102mm
<b>Adhesion:</b>		
<b>Peel:</b>	120 oz/inch width	33.9 N/2.5 cm
<b>Shear - Indefinite @:</b>	2 psi	13.8 kPa
<b>Temperature Resistance:</b>	-37°F to 275°F	-38°C to 135°C
<b>Minimum Application Temperature:</b>	-20°F	-29°C
<b>Release Liner:</b>	55 lb Moisture Stable Glassine	90 GSM

#### **IMPORTANT INFORMATION:**

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

12/26/90