



30 Commerce Road  
Rockland, MA 02370

Phone: 1-800-343-1076  
Fax: 781-871-0065

## Technical Data Sheet

**Product No.:** **909**  
**Description:** A 2.5 mil (62.5 micron) strong and conformable transparent polyethylene film tape with a very high tack, UV resistant acrylic adhesive. This product has excellent peel adhesion and cold stick as well as excellent resistance to moisture, acids, chemicals, oils, abrasion, and weathering.  
**Applications:** Primarily used for film can sealing and ink container sealing.

	Technical Data	
	Imperial	Metric
<b>Adhesive thickness:</b>	1.5 mils (0.0015")	
<b>Substrate Thickness:</b>	2.5 mils (0.0025")	
<b>Peel Adhesion (PSTC-1):</b>	60 oz/inch	17 N/2.5 cm
<b>Shear Adhesion (PSTC-7):</b>	Indefinite @ 2.2 psi	Indefinite @ 15.2 kPa
<b>Tensile (PSTC-31):</b>	8 lbs/inch width	36.1 N/2.5 cm
<b>Elongation:</b>		
<b>Maximum continuous use Temperature:</b>	250°F	120°F
<b>Minimum application temperature:</b>	10°F	-12°C

The information listed is in good faith and has been established from sources believed to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities.