



30 Commerce Road
Rockland, MA 02370

Phone: 1-800-343-1076
Fax: 781-871-0065

Technical Data Sheet

917

SHRINK FILM SPLICING TAPE

DESCRIPTION: A 7 mil (175 micron) thick white UV stable polyethylene film coated with a high quick stick, synthetic rubber based adhesive system. The adhesive has excellent shear strength and good high temperature resistance with clean removability from fiberglass, stainless steel and aluminum after long term outdoor exposure.

APPLICATIONS: Designed specifically for temporary hull attachment and patching of heavy gauge shrink film used in both the marine and manufactured housing industry. Also widely used for preservation sealing of canisters and other containers

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness:	8.1 mils	0.2057 mm
Adhesion:		
Peel (PSTC-101)	27 oz/inch width	7.6 N/2.5 cm
Shear (PSTC-107)	indefinite @ 2.2 psi	indefinite @ 15.2 kPa
Tensile: (PSTC-131)	19 lbs/inch width	85.9 N/2.5 cm
Elongation: (PSTC-131)	400%	400%
Temperature Resistance:	175°F	80°C
Minimum Application Temperature:	40°F	4°C

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities.