

# 921CW

## CLEAR POLYETHYLENE TAPE

---

**DESCRIPTION:** A 5 mil (125 micron) thin, strong and conformable transparent polyethylene film tape coated with a very high shear, UV resistant cold weather acrylic adhesive with excellent holding properties and cold stick. Excellent resistance to moisture, acids, chemicals, alkalis, oils, abrasion and weathering.

**APPLICATIONS:** Primarily used for splicing polyethylene film. Also used as a weather seal for applying plastic storm windows, door jams, window casings in low temperature environments as well as for film can sealing and ink container sealing.

### TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
<b>Thickness:</b>	5.9 mils (0.0059")	0.1499 mm
<b>Adhesion:</b>		
<b>Peel (PSTC#1):</b>	75 oz/inch width	20.8 N/2.5 cm
<b>Hold(PSTC#7): 96+hrs@</b>	2.2 psi	15.2 kPa
<b>Tack(PSTC#6): rolling ball</b>	2 inch	50.8 mm
<b>Tensile:</b>	12.5 lbs/inch width	55.6 N/2.5 cm
<b>Elongation:</b>	250%	250%
<b>Minimum Application</b>		
<b>Temperature:</b>	-10°F	-23°C
<b>High Temperature</b>		
<b>Resistance:</b>	175°F	80°C

**IMPORTANT INFORMATION:**

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 1/28/00